

MATERIAL SAFETY DATA SHEET

Product Identifier Product #6000 - Dura-Coat Acrylic Roof Coating					NIIFIC	[WHMIS Class D - Po	oisonous ar	n] and Infectious Materials - Division 2
Product Use						- Subdivision	JR	
White reflective roof coating								
Manufacturer's Name				Supplier's Name			-	
Tucson Rubberized Coatings				<u> </u>				
Street Address				Street Address				
6351 S. Tucson Blvd City		Province		City				Province
·				Oity				1 TOVINGE
Tucson Postal Code	Emergenc	Arizona Emergency Telephone		Postal Code En		Emergen	ncy Telephone	
85706	520-293-	3-7000						
Date MSDS Prepared		MSDS Pre	epared By		Phone Nur		nber	
5/20/2020		CEO						
SECTION 2 — COMPOS	ITION/	INFORI	MATION C	—— ON INGREI	— DIENTS			
Hazardous Ingredients (specific)	C	% (weight)	CAS Number L		LD 50 of Ir	LD 50 of Ingredient (specify species and route		LC 50 of Ingredient (specify species)
crylic Polymer Solution		35-50%						cpcoics,
Calcium Carbonate		15-30%						
itanium Dioxide		5-20%	13463-67-7					
Ethylene Glycol		1-2.5%	107-21-1					Ingestion/Oral-Rat LD50-20g/kg
Texanol Ester		0.1-1.5%						Ingestion/Oral-Rat LD50-3200 mg/kg
SECTION 3 — HAZARDS	3 IDEN	TIFICA	TION					
Route of Entry Skin Contact X	Skin Absorption	ion 🗓	Eye Contact	Inhalation	☑ Inge	estion		
Emergency Overview] WARNING: Causes mild ski	in irritation. F	Harmful if swall	lowed. Do not hand	dle until all safety pre	ecautions have	e been read a	nd understr	ood.
WHMIS Symbols] Class D - Poisonous and Info	iectious Mate	erials - Division	ı 2 - Subdivision B					
Potential Health Effects Inhalation of vapors may cause	se central nerv	vous system dep	pression, light-headed	iness, headache, naus	ea and loss of o	oordination. Ma	ay cause skir	n irritation.
Likely to cause eye irritation,	burning, tearin	ng etc on contac	t with eyes. If irritation	n persists, seek medica	al attention. Inge	estion may caus	e irritation. N	May be harmful or fatal if swallowed.
SECTION 4 — FIRST AID) MEAS	SURES						
Skin Contact If skin irritation occurs get medical a	attention/advic	ce						
Eye Contact Rinse cautiously with water for sever	eral minutes. R	temove any conf	tact lenses.					
Inhalation * Inhalation of vapors o * Under normal condition				pression, light-head	.edness, heada	ache, nausea	and loss of	f coordination.
Ingestion Get medical attention immediately							-	

57M6 (6/99)



Product Identifier-2-

SECTION 5 — FIRE FIGHTING MEASURES

☐ Yes		If yes, under which conditions?	
	x No		
Means of Extinction			
Water spray, fog or regular foam	1		
Flashpoint (° C) and Method		Upper Flammable Limit (% by volume)	Lower Flammable Limit (% by volume)
>241 degrees F			
Autoignition Temperature (°C	()	Explosion Data — Product containers may to prevent release of materials.	rupture when exposed to extreme heat. Precautions should be taken
Hazardous Combustion Prod	lucts		
*	Non-combustible, subst	tance itself does not burn but may decompose up	pon heating to produce toxic fumes.
[NFPA]	•		
Leak and Spill Procedures	CCIDENTAL K	ELEASE MEASURES	
· ·	or spilled material unless wearing appropria	ate	
		propriate	
	nd or other non-combustible material and tra	ansfer to	
containers.			
containers. Use appropriate Personal Protectiv Avoid contact with strong oxidizing	re Equipment (PPE) g agents and acids		
Use appropriate Personal Protectiv Avoid contact with strong oxidizing	g agents and acids		
Use appropriate Personal Protectiv Avoid contact with strong oxidizing	g agents and acids) STORAGE	
Use appropriate Personal Protectiv Avoid contact with strong oxidizing	IANDLING AND) STORAGE	
Use appropriate Personal Protectiv Avoid contact with strong oxidizing SECTION 7 — H	IANDLING AND) STORAGE	
Use appropriate Personal Protectiv Avoid contact with strong oxidizing SECTION 7 — H Handling Procedures and Equipr KEEP OUT OF THE REACH OF CHILD	IANDLING AND) STORAGE	
Use appropriate Personal Protectiv Avoid contact with strong oxidizing SECTION 7 — H Handling Procedures and Equipr KEEP OUT OF THE REACH OF CHILD	IANDLING AND) STORAGE	
Use appropriate Personal Protectiv Avoid contact with strong oxidizing SECTION 7 — H Handling Procedures and Equipr KEEP OUT OF THE REACH OF CHILD when not in use	JANDLING AND ment DREN! Keep containers tightly closed	STORAGE	
Use appropriate Personal Protectiv Avoid contact with strong oxidizing SECTION 7 — H Handling Procedures and Equipr KEEP OUT OF THE REACH OF CHILD when not in use Storage Requirements Avoid extreme temperatures and freezing	JANDLING AND ment DREN! Keep containers tightly closed	STORAGE	
Use appropriate Personal Protectiv Avoid contact with strong oxidizing SECTION 7 — H Handling Procedures and Equipr KEEP OUT OF THE REACH OF CHILD when not in use Storage Requirements Avoid extreme temperatures and freezing	JANDLING AND ment DREN! Keep containers tightly closed	STORAGE	

SECTION 8 — EXPOSURE CONTROL / PERSONAL PROTECTION

	Result	Canada Ontario	Mexico	NIOSH	OSHA
Ethylene Glycol (107-21-1)		50 ppm TWAEV (total aerosol and vapour); 155 mg/m3 TWAEV (total aerosol and vapour); 10 mg/m3 TWAEV (for assessing the visibility in a work environment, aerosol only)	Not established	Not established	Not established
Titanium Dioxide (13463-67-7)	TWAs	10 mg/m3 TWAEV (total dust)	10 mg/m3 TWA (as Ti)	Not established	15 mg/m3 TWA (total dust)
Isopropyl Alcohol (67-63-0)	TWAs	980 mg/m3	900 mg/m3	980 mg/m3	980 mg/m3
Calcium Carbonate (1317-65-3)	TWAs	Not established	10 mg/m3 TWA	10 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable dust)	15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

Personal Protective Equipment	☑ Gloves	☐ Respirator	🗷 Eye	▼ Footwear	☑ Clothing	☐ Other
If checked, please specify type	Recommend	gloves, eye protection, clothes ar	nd shoes when handling			

Product Identifier-3-

SECTION 9 — PHYSICAL AND	CHEMICAL PROPERTIES			
Physical State	Odour and Appearance	Odour Threshold (ppm)		
Liquid	Paint like order	No Data		
Specific Gravity	Vapour Density (air = 1)	Vapour Pressure (mmHg)		
>1.28	>1	No Data		
Evaporation Rate	Boiling Point (° C)	Freezing Point (° C) <32 Degrees F		
	>200 degrees F			
pH >8.5	Coefficient of Water/Oil Distribution	[Solubility in Water]		
SECTION 10 — STABILITY AN	ID REACTIVITY			
Chemical Stability	If no, under which conditions?			
☑ Yes ☐ No				
Incompatibility with Other Substances	If yes, which ones?			
🗵 Yes 🗖 No	* Strong oxidizers and	acids.		
Reactivity, and under what conditions? Avoid	Excessive heat and freezing.			
Γ				
Hazardous Decomposition Products No known	issues under normal usage conditions.			
Trazardous Bessimposition Freducts 140 kilomi	100000 dilati normal deage conditions.			
SECTION 11 — TOXICOLOGIC	CAL INFORMATION			
Effects of Acute Exposure Titanium	Dioxide (10% TO 20%) 13463-67-7 Acute Toxicity: orl-rat TDI	Lo:60 am/ka:		
Irritation:	skn-hmn 300 ug/3D-I MLD			
	Glycol (0.25% TO 2.5%) 107-21-1 kicity: orl-rat LD50:20 gm/kg; skn-hmn TCLo:10 pph; skn-hmn	TDLo:5		
mg/kg/7D-l; Irritation: skn-hmn 500 mg/7D MLD				
Texanol Ester (0.1% TO 1.5%) 25265-77-4 Acute Toxicity: orl-rat LD50:3200 mg/kg; ihl-rat LC :>3500 mg/				
Effects of chronic exposure				
No Data Available				
Product Identifier-4-				
SECTION 12 — ECOLOGICAL	INICODMATION			
[Aquatic Toxicity]	INFORMATION			
No Data Avaliable				
<u> </u>				
SECTION 13 — DISPOSAL CC	NSIDERATIONS			
Waste Disposal Dispose in accordance with local regul	ations			
Dispose in accordance with local regul				

SECTION 14 — TRANSPORT INFORMATION

Special	Shipping Information		
			PIN
TDG	Canada - Transportation of Dangerous Goods - Shipping Name: Not Restricted.	[DOT] United States - Department of Transportation - Shipp	ing Name: Not Regulated.
[IMO]	International Maritime Transport Shipping Name: Not Regulated.	[ICAO]	

SECTION 15 — REGULATORY INFORMATION

United States

Environment

U.S. - CERCLA/SARA - Hazardous Substances and their Reportable Quantities

Calcium Carbonate
 Titanium Dioxide
 Ethylene Glycol
 Isopropyl Alcohol
 Texanol Ester
 Hydroxyethylcellulose
 1317-65-3
 15% TO 30%
 Not Listed
 Not Listed
 107-21-1
 0.25% TO 2.5%
 Not Listed
 Not Listed

United States - California

Environment

U.S. - California - Proposition 65 - Carcinogens List

Calcium Carbonate
 Titanium Dioxide
 Ethylene Glycol
 Isopropyl Alcohol
 Texanol Ester
 Hydroxyethylcellulose
 1317-65-3
 15% TO 30%
 Not Listed
 TO 2.5% TO 2.5%
 Not Listed
 O.1 TO 2%
 Not Listed
 Not Listed
 Not Listed
 O.1% TO 1%
 Not Listed
 Not Listed
 Not Listed

United States - Rhode Island

Labor

U.S. - Rhode Island - Hazardous Substance List

Calcium Carbonate
 Titanium Dioxide
 Ethylene Glycol
 Isopropyl Alcohol
 Texanol Ester
 Hydroxyethylcellulose
 1317-65-3
 15% TO 30%
 Not Listed
 Not Listed
 107-21-1
 0.25% TO 2.5%
 Not Listed
 Not Listed
 Not Listed
 Not Listed
 Not Listed
 Not Listed
 Not Listed

Inventory					
Component	CAS	EU EINECS	TSCA		
Water	7732-18-5	Yes	Yes		
Acrylic Polymer Solution	NDA	No	No		
Calcium Carbonate	1317-65-3	Yes	Yes		
Titanium Dioxide	13463-67-7	Yes	Yes		
Hydroxyethylcellulose	9004-62-0	No	Yes		
Ethylene Glycol	107-21-1	Yes	Yes		
Surfactant/Additive	NDA	No	No		
Isopropyl Alcohol	67-63-0	Yes	Yes		
Texanol Ester	25265-77-4	Yes	Yes		

SECTION 16 — OTHER INFORMATION

Preparation date - 5/20/2020

This information relates to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of our knowledge and belief, accurate and reliable as of the date compiled. However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the users responsibility to verify the suitability and completeness of such

information for particular use. Tucson Rubberized Coatings does not accept liability for any loss or damage that may occur from the use of this information.