



F30-4869

30LB FELT PAPER 4869

DESCRIPTION:

F30-4869 is an industry leading, superior quality "authentic" asphalt saturated organic felt underlayment. Manufactured to ASTM 4869 type II specifications.

USES:

F30-4869 authentic asphalt saturated organic felt underlayment is used as a **breathable** secondary weather resistant barrier when applied over the roof deck prior to the installation of the primary roofing product.

FEATURES AND BENEFITS:

- **Required:** (Note: Approved underlayment is required to validate warranty on most all roofing systems.)
- **Compatible:** Recommended for use as an upgrade to 15 ASTM D 226 for asphalt shingle applications. May also be used with other roofing systems when ASTM D226 is not required.
- **Easy to Apply:** No special fasteners required.
(Note: Plastic cap nails help seal around nail holes.)
- **Cost Effective:** Convenient roll size, **200 sq ft. coverage with salvage edge**, minimizes job loss and excessive waste.
- **Permeable:** Breathable membrane to help prevent dry rot, mold, and other structural damages.
- **Walk-able:** Natural non-skid surface; ideal for steep slope roofing.
- **Durable:** Manufactured for maximum performance.
- **Eco-Friendly:** Organic dry felt is made from **100% post consumer recycled material** and domestic asphalt from a local source.
(Note: Leed points may be available.)

PRODUCT INFORMATION:

- Width: 39 3/8 Inches
- Coverage: 216 Sq. Ft.

APPROVALS & CERTIFICATIONS:

ASTM D 4869, Type II



LIMITED WARRANTY AND DISCLAIMER:

To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact TRC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with TRC warranty procedures and program. For limited manufacturer's warranty and disclaimer information, visit our website at: www.rubberized.com.