

600-T TUFF-TEX RUBBERIZED SYNTHETIC STUCCO

DESCRIPTION:

PRODUCT NO. 600-T creates a thick rubber-like shield of protection which is highly resistant to cracking or chipping. This product also contains bonding agents which give it excellent adhesion and ceramics for insulating properties.

USES:

PRODUCT NO. 600-T is excellent for use as a complete interior or exterior wall finish, as well as for repairing existing walls. It is paintable or you may have it pre-tinted to a color of our choice to eliminate expensive repainting. PRODUCT NO. 600-T can be applied in various types of finishes and is ideal for beautifying virtually any surface, such as existing stucco, masonry, block, brick, metal, plywood, OSB, or wood siding.

SURFACE PREPARATION:

All surfaces must be dry and free of dust, oil, loose granules or peeling paint and all other foreign matter. Surface should be prepared by either wire brushing, sanding or power washing. All cracks, joints or uneven surfaces should be filled with PRODUCT NO. 501-W-P Patching Compound prior to application of PRODUCT NO. 600-T for filling hairline cracks, waterproofing and providing additional insulation.

APPLICATION:

Power mix product to an even mixture. Apply to surface with a stiff brush, roller, trowel, or hopper gun depending on desired surface. Keep the brush or roller moist for easy application. Apply PRODUCT NO. 600-T at a rate of 5-8 gallons per 100 sq. ft. depending on desired thickness and finish. This product should not be applied when rain or frost is forecast within 24 hours. Apply only when the temperature is 55 degrees and rising.

KEEP THIS PRODUCT FROM FREEZING.

STORAGE:

Product should be stored in a clean and dry area, away from direct sunlight and protected from freezing.

CLEAN-UP:

Clean brushes, tools and other equipment with warm soapy water immediately after use. Dried film may require paint remover.

PHYSICAL PROPERTIES:

Solids by Weight (%)	79%
Weight Per Gallon	15.7 lbs.
Drying Time	At 50% relative humidity and 70°F; Touch: 2-3 hrs
Silicone (%)	None
Flammability	None
VOC	< 150 g/l
Viscosity	120 KU

**NOTE: Percentages stated are + or - 5% Approx. Shipping Weights:
(All approximate weights include container)*

5-gallon bucket weight approximately 80 lbs

HANDLING PRECAUTIONS:

Product safety information required for safe use is not included. Before handling, read product safety data sheets and container labels for safe use, physical and health hazard information. Safety data sheets are available on the TRC website at www.rubberized.com. You can also obtain a copy from one of our local TRC stores.

LIMITED WARRANTY AND DISCLAIMER:

To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact TRC to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with TRC warranty procedures and program. For limited manufacturer's warranty and disclaimer information, visit our website at: www.rubberized.com.