



DESCRIPTION

A homogenous blend of selected petroleum bitumen, water and non-asbestos mineral stabilizers. PT Asphalt Emulsion is a premium, versatile coating for the protection of roofing materials, metal, and masonry surfaces. It has excellent weathering capabilities and therefore can also be used for damp proofing above grade foundation walls, sealing masonry surfaces and retaining walls and as an anti-corrosive wood, metal, and pipe coating. The dried film cures to a tough, flexible, durable finish and will resist extreme variations in temperature and weather.

USES

As a protective coating for new or existing composition roofs with smooth (non-graveled) surfaces, metal roofs and cured solvent borne primers and coatings. With reinforcing fabrics over medium to severely alligatored asphalt flood coats. Damp proofing of masonry and concrete surfaces. PT Non-Fibered Emulsion is a vapor retarder and anti-corrosive used as a protective coating against dampness on the exterior face of interior walls in cavity wall construction and exterior surfaces of concrete, metal and wood above grade. Damp-proofing exterior below-grade foundations and walls.

CLEAN UP

Use soap and warm water.

APPLICATION RATE

Apply to the prepared surface at a rate of 2-4 gallons per 100 square feet. To avoid pinholes and ensure maximum performance, application of two coats, each at 1/2 the total coverage rate and applied perpendicular to one another, are recommended. (First coat must be allowed to dry prior to the application of the second coat).

SPRAY INFO: 1000-1500 PSI, .061-.099 Tip Size, 3-6 GPM

APPLICABLE STANDARDS

Exceeds performance requirements of ASTM D1227, TYPE III, Class I. UL CLASS A RATED.

VOC content: <20 g/l

PACKAGING: Available in 5-gallon pails (45lbs) and 55-gallon drums (507lbs). If further information is needed, contact Perma Tech Roofing Technical services at (520) 293-7000

SAFETY AND ENVIRONMENTAL: CONSULT MATERIAL DATA SAFETY SHEET FOR DETAILED HANDLING AND DISPOSAL

- | | |
|------------|-----------|
| • Contents | CAS# |
| • Asphalt | 8052-42-4 |
| • Clay | 1302-78-9 |
| • Water | 7732-18-5 |

APPLICABLE METHODS



LIMITED WARRANTY & DISCLAIMER

To the best of our knowledge, the technical data contained herein is true and accurate at the date of issuance and is subject to change without prior notice. User must contact Perma-Tech Roofing Supply to verify correctness before specifying or ordering. No guarantee of accuracy is given or implied. Liability, if any, is limited to replacement of product unless installed by an approved contractor in accordance with Perma-Tech Roofing Supply warranty procedures and program. For limited manufacturer's warranty and disclaimer information, visit our website at: www.permatechroofing.com.